

204222 - Fundamentals of Database Systems

Chapter 3

The Relational Data Model and Relational Database Constraints

Adapted for 204222

by Areerat Trongratsameethong

Chapter 3 Outline

- The Relational Data Model and Relational Database Constraints
- Relational Model Constraints and Relational Database Schemas
- Update Operations, Transactions, and Dealing with Constraint Violations

The Relational Data Model and Relational Database Constraints

- Relational model
 - First commercial implementations available in early 1980s
 - Has been implemented in a large number of commercial system
- Hierarchical and network models
 - Preceded (มาก่อน) the relational model

Relational Model Concepts

- Represents data as a collection of relations
- **Table** of values
 - Row
 - Represents a collection of related data values
 - Fact that typically corresponds to a real-world entity or relationship
 - *Tuple*
 - Table name and **column** names
 - Interpret the meaning of the values in each row
attribute

Relational Model Concepts (cont'd.)




Figure 3.1

The attributes and tuples of a relation STUDENT.

Domains, Attributes, Tuples, and Relations

- **Domain D**
 - Set of atomic (indivisible) values
- **Atomic**
 - Each value indivisible (แบ่งแยกไม่ได้)
- **Specifying a domain**
 - **Data type** specified for each domain: แต่ละ domain ต้องมีการกำหนดลักษณะของข้อมูล

Domains, Attributes, Tuples, and Relations (cont'd.)

- **Relation schema R**
 - Denoted by $R(A_1, A_2, \dots, A_n)$
 - Made up of a relation name R and a list of attributes, A_1, A_2, \dots, A_n
 - Relation schema ประกอบด้วย ชื่อ relation R และ attributes A_1, A_2, \dots, A_n ของ R
 - แต่ละ Relation อยู่ในรูป $R(A_1, A_2, \dots, A_n)$
- **Attribute A_j**
 - Name of a role played by some domain D in the relation schema R
- **Degree (or arity) of a relation**
 - Number of attributes n of its relation schema

Domains, Attributes, Tuples, and Relations (cont'd.)

- **Relation (or relation state):** Relation State คือสถานะของข้อมูลใน Relation ณ เวลาใดเวลาหนึ่ง ซึ่งแทนด้วย set ของ tuple (หรือ record) อยู่ในรูปแบบ $r = \{t_1, t_2, \dots, t_m\}$
 - Set of **n -tuples** $r = \{t_1, t_2, \dots, t_m\}$
 - Each n -tuple t
 - Ordered list of n values $t = \langle v_1, v_2, \dots, v_n \rangle$
 - Each value $v_i, 1 \leq i \leq n$, is an element of $\text{dom}(A_i)$ or is a special NULL value

Domains, Attributes, Tuples, and Relations (cont'd.)

- **Current relation state**
 - Relation state at a given time
 - Reflects only the valid tuples that represent a particular state of the real world
- **Attribute names**
 - Indicate different **roles**, or interpretations, for the domain

Characteristics of Relations (cont'd.)

Figure 3.2

The relation STUDENT from Figure 3.1 with a different order of tuples.

STUDENT

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	(817)749-1253	25	3.53
Barbara Benson	533-69-1238	(817)839-8461	7384 Fontana Lane	NULL	19	3.25
Rohan Panchal	489-22-1100	(817)376-9821	265 Lark Lane	(817)749-6492	28	3.93
Chung-cha Kim	381-62-1245	(817)375-4409	125 Kirby Road	NULL	18	2.89
Benjamin Bayer	305-61-2435	(817)373-1616	2918 Bluebonnet Lane	NULL	19	3.21




Figure 3.1

The attributes and tuples of a relation STUDENT.

Characteristics of Relations (cont'd.)

- Values and NULLs in tuples
 - Each value in a tuple is atomic
 - **Flat relational model**
 - Composite and multivalued attributes not allowed
 - First normal form assumption
 - Multivalued attributes
 - Must be represented by separate relations
 - Composite attributes
 - Represented only by simple component attributes in basic relational model

Characteristics of Relations (cont'd.)

- NULL values
 - Represent the values of attributes that may be unknown or may not apply to a tuple
 - Meanings for NULL values
 - *Value unknown*
 - *Value exists but is not available (บอกไม่ได้)*
 - *Attribute does not apply to this tuple (also known as value undefined) ไม่ได้กำหนด*

Characteristics of Relations (cont'd.)

- Interpretation (meaning) of a relation
 - **Assertion**
 - Each tuple in the relation is a **fact** or a particular instance of the assertion
 - **Predicate**
 - Values in each tuple interpreted as values that satisfy predicate (state)

Relational Model Notation

- Relation schema R of degree n (n attributes)
 - Denoted by $R(A_1, A_2, \dots, A_n)$
- Uppercase letters Q, R, S
 - Denote relation names
- Lowercase letters q, r, s
 - Denote relation states (เช่น $r = \{t_1, t_2, \dots, t_m\}$)
- Letters t, u, v
 - Denote tuples (หรือ record หรือ row)

Relational Model Notation

- Name of a relation schema: STUDENT
 - Indicates the current set of tuples in that relation
- Notation: STUDENT(Name, Ssn, ...)
 - Refers only to relation schema
- Attribute A can be qualified with the relation name R to which it belongs
 - Using the dot notation $R.A$ (A คือ attribute ของ R)

Relational Model Notation

- *n-tuple* t in a relation $r(R)$
 - Denoted by $t = \langle v_1, v_2, \dots, v_n \rangle$
 - v_i is the value corresponding to attribute A_i
- Component values of tuples:
 - $t[A_i]$ and $t.A_i$ refer to the value v_i in t for attribute A_i
: $t[A_i]$ and $t.A_i$ หมายถึง ค่าที่อยู่ใน attribute A_i ของ tuple t
 - $t[A_u, A_w, \dots, A_z]$ and $t.(A_u, A_w, \dots, A_z)$ refer to the subtuple of values $\langle v_u, v_w, \dots, v_z \rangle$ from t corresponding to the attributes specified in the list

Relational Model Constraints

- Constraints

- Restrictions on the actual values in a database

- state: กำหนดข้อบังคับของข้อมูลที่จะเข้าไปอยู่ในฐานข้อมูล

- Derived from the rules in the miniworld that the

- database represents: ข้อบังคับได้มาจากความเป็นจริงของข้อมูล

- เช่น อายุของสิ่งมีชีวิตมีค่า > 0

- **Inherent model-based constraints or implicit constraints**

- Inherent in the data model: ได้รับสืบทอดมาจากข้อบังคับของ

- แต่ละ data model

Relational Model Constraints (cont'd.)

- **Schema-based constraints or explicit constraints**
 - Can be directly expressed in schemas of the data model: กฎข้อบังคับที่สามารถกำหนดโดยตรงใน data model หรือ database schema
- **Application-based or semantic constraints or business rules**
 - Cannot be directly expressed in schemas
 - Expressed and enforced by application program
กฎข้อบังคับที่ไม่สามารถกำหนดโดยตรงใน data model หรือ database schema จะถูกกำหนดไว้ใน application program แทน เช่น ห้ามเบิก OT เกิน 4 ชั่วโมงในวันธรรมดา

Domain Constraints

- Typically include:
 - Numeric data types for integers and real numbers
 - Characters
 - Booleans
 - Fixed-length strings
 - Variable-length strings
 - Date, time, timestamp
 - Money
 - Other special data types

Key Constraints and Constraints on NULL Values

- No two tuples can have the same combination of values for all their attributes.
- **Superkey**
 - No two distinct tuples in any state r of R can have the same value for SK
- **Key**
 - Superkey of R
 - Removing any attribute A from K leaves a set of attributes K that is not a superkey of R any more

Key Constraints and Constraints on NULL Values (cont'd.)

- Key satisfies two properties:
 - Two distinct tuples in any state of relation cannot have identical values for (all) attributes in key
 - Minimal superkey
 - Cannot remove any attributes and still have uniqueness constraint in above condition hold

Key Constraints and Constraints on NULL Values (cont'd.)

- **Candidate key**
 - Relation schema may have more than one key
- **Primary key** of the relation
 - Designated among candidate keys
 - Underline attribute
- Other candidate keys are designated as **unique keys**

Key Constraints and Constraints on NULL Values (cont'd.)

CAR

<u>License_number</u>	Engine_serial_number	Make	Model	Year
Texas ABC-739	A69352	Ford	Mustang	02
Florida TVP-347	B43696	Oldsmobile	Cutlass	05
New York MPO-22	X83554	Oldsmobile	Delta	01
California 432-TFY	C43742	Mercedes	190-D	99
California RSK-629	Y82935	Toyota	Camry	04
Texas RSK-629	U028365	Jaguar	XJS	04

Figure 3.4

The CAR relation, with two candidate keys: License_number and Engine_serial_number.

Relational Databases and Relational Database Schemas

- **Relational database schema S**
 - Set of relation schemas $S = \{R_1, R_2, \dots, R_m\}$
 - Set of integrity constraints IC
- **Relational database state**
 - Set of relation states $DB = \{r_1, r_2, \dots, r_m\}$
 - Each r_i is a state of R_i and such that the r_i relation states satisfy integrity constraints specified in IC

Relational Databases and Relational Database Schemas (cont'd.)

- **Invalid state**
 - Does not obey all the integrity constraints
- **Valid state**
 - Satisfies all the constraints in the defined set of integrity constraints IC


Integrity, Referential Integrity, and Foreign Keys

- **Entity integrity constraint**
 - No primary key value can be NULL
- **Referential integrity constraint**
 - Specified between two relations
 - Maintains consistency among tuples in two relations

Integrity, Referential Integrity, and Foreign Keys (cont'd.)

- **Foreign key rules:**

- The attributes in FK have the same domain(s) as the primary key attributes PK
- Value of FK in a tuple t_1 of the current state $r_1(R_1)$ either occurs as a value of PK for some tuple t_2 in the current state $r_2(R_2)$ or is NULL



StudentID (PK)

FacultyID (FK):


- ต้องมีรหัส FacultyID อยู่ใน Faculty

- หรือมีรหัส FacultyID ใน Student เป็น NULL

FacultyID (PK): PK ห้ามเป็น NULL

Integrity, Referential Integrity, and Foreign Keys (cont'd.)

- Diagrammatically display referential integrity constraints
 - Directed arc from each foreign key to the relation it references
- All integrity constraints should be specified on relational database schema



Other Types of Constraints

- Semantic integrity constraints
 - May have to be specified and enforced on a relational database
 - Use **triggers**: ដាក់ Insert Update Delete and **assertions**: a statement that tests a database condition e.g. check to make sure that total loan never exceeds the total amount in the bank
 - More common to check for these types of constraints within the application programs

Other Types of Constraints (cont'd.)

- Functional dependency constraint
 - Establishes a functional relationship among two sets of attributes X and Y
 - Value of X determines a unique value of Y
 - จะได้เรียนใน FD และ Normalization
- **State constraints**
 - Define the constraints that a valid state of the database must satisfy
- **Transition constraints**
 - Define to deal with state changes in the database

Update Operations, Transactions, and Dealing with Constraint Violations

- Operations of the relational model can be categorized into retrievals and updates
- Basic operations that change the states of relations in the database:
 - Insert
 - Delete
 - Update (or Modify)

Figure 3.6

One possible database state for the COMPANY relational database schema.

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

Figure 3.6

One possible database state for the COMPANY relational database schema.

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

PROJECT

<u>Pname</u>	<u>Pnumber</u>	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------




Figure 3.7

Referential integrity constraints displayed on the COMPANY relational database schema.

The Insert Operation

- Provides a list of attribute values for a new tuple t that is to be inserted into a relation R
- Can violate any of the four types of constraints
- If an insertion violates one or more constraints
 - Default option is to reject the insertion

The Delete Operation

- Can violate (ขัดแย้ง) only referential integrity
 - If tuple being deleted is referenced by foreign keys from other tuples
 - **Restrict**
 - Reject the deletion
 - **Cascade**
 - Propagate the deletion by deleting tuples that reference the tuple that is being deleted
 - **Set null or set default**
 - Modify the referencing attribute values that cause the violation

The Update Operation

- Necessary to specify a condition on attributes of relation
 - Select the tuple (or tuples) to be modified
- If attribute not part of a primary key nor of a foreign key
 - Usually causes no problems
- Updating a primary/foreign key
 - Similar issues as with Insert/Delete

Not Null

Referential Integrity Constraint

The Transaction Concept

- **Transaction**
 - Executing program
 - Includes some database operations
 - Must leave the database in a valid or consistent state
- **Online transaction processing (OLTP) systems**
 - Execute transactions at rates that reach several hundred per second

Summary

- Characteristics differentiate relations from ordinary tables or files
- Classify database constraints into:
 - Inherent model-based constraints, explicit schema-based constraints, and application-based constraints
- Modification operations on the relational model:
 - Insert, Delete, and Update