

204320 - Database Management

Chapter 24

Database Security

Adapted for 204320

by Areerat Trongratsameethong

Outline

- 1 Database Security and Authorization
- 2 Discretionary Access Control

1. Introduction to Database Security Issues

- Types of Security
 - Legal (ถูกกฎหมาย) and ethical (จริยธรรม) issues
 - Policy issues
 - System-related issues: เช่น การป้องกันระดับ OS, account
เข้า Windows, Folder, ...
 - The need to identify multiple security levels: เช่น
Top Secret, Secret, Medium, ...

1. Introduction to Database Security Issues (2)

- Threats (การคุกคาม) to databases
 - **Loss of integrity** (ความถูกต้องของข้อมูล เสียหายจากคนที่ไม่ได้สิทธิ์เข้าถึงข้อมูล)
 - **Loss of availability** (ความพร้อมใช้งาน คนที่มีสิทธิ์เข้าถึงข้อมูลกลับไม่สามารถใช้งานข้อมูลที่เกี่ยวข้องได้)
 - **Loss of confidentiality** (ความลับ ข้อมูลที่เป็นความลับถูกคนที่ไม่ได้สิทธิ์เข้าถึงข้อมูล เข้าถึงข้อมูลได้ เช่น ข้อมูลเงินเดือน ถูกคนที่ไม่ได้สิทธิ์ hack เข้าไปได้)
- To protect databases against these types of threats four kinds of countermeasures (ตอบโต้) can be implemented:
 - **Access control:** การควบคุมการเข้าถึงข้อมูล
 - **Inference control:** การควบคุมเชิงอนุมาน เช่นเช่น ระบบฐานข้อมูลประชากรที่นำเสนอข้อมูลสถิติของประชากร การควบคุมเชิงอนุมาน จะกำหนดสิทธิ์ไม่ให้คนที่ไม่ใช่เจ้าของข้อมูลเห็นรายละเอียดข้อมูลของประชากรแต่ละคน
 - **Flow control:** ควบคุมการไหลของข้อมูลไปยังคนที่ไม่ได้สิทธิ์
 - **Encryption:** การเข้ารหัสข้อมูล

1. Introduction to Database Security Issues (3)

- A DBMS typically includes a database security and authorization subsystem that is responsible for ensuring the security portions of a database against unauthorized access.
- Two types of database security mechanisms:
 - **Discretionary** security mechanisms: ให้สิทธิ ยกเลิกสิทธิ การเข้าถึงข้อมูลในฐานะข้อมูล
 - **Mandatory** security mechanisms: Multilevel Control (enforcing multiple levels of security)



1. Introduction to Database Security Issues (4)

- The security mechanism of a DBMS must include provisions for restricting access to the database as a whole
 - This function is called access control and is handled by creating user accounts and passwords to control login process by the DBMS.

การควบคุมการเข้าถึงข้อมูล ผ่านการให้สิทธิ และยกเลิกสิทธิ

1. Introduction to Database Security Issues (5)

- The security problem associated with databases is that of controlling the access to a **statistical database**, which is used to provide statistical information or summaries of values based on various criteria.
 - The countermeasures to statistical database security problem is called **inference control measures**.

เช่น ระบบฐานข้อมูลประชากรที่นำเสนอข้อมูลสถิติของประชากร การควบคุมเชิง
อนุมาน จะกำหนดสิทธิไม่ให้คนที่ไม่ใช่เจ้าของข้อมูลเห็นรายละเอียดข้อมูลของ
ประชากรแต่ละคน

1. Introduction to Database Security Issues (6)

- Another security is that of **flow control**, which prevents information from flowing in such a way that it reaches unauthorized users.
- Channels that are pathways for information to flow implicitly in ways that violate the security policy of an organization are called **covert channels**.
- **covert channels:** การไหลของข้อมูลที่ละเมิดความปลอดภัย คือ ไหลไปยังคนที่ไม่มีความสามารถในการเข้าถึงข้อมูล

1. Introduction to Database Security Issues (7)

- A final security issue is **data encryption**, which is used to protect sensitive data (such as credit card numbers) that is being transmitted via some type communication network.
- The data is **encoded** using some **encoding algorithm**.
 - An unauthorized user who access encoded data will have difficulty deciphering it, but authorized users are given decoding or decrypting algorithms (or keys) to decipher (ถอดรหัส) data.

1.2 Database Security and the DBA

- The database administrator (**DBA**) is the central authority for managing a database system.
 - The DBA's responsibilities include
 - granting privileges to users who need to use the system
 - classifying users and data in accordance with the policy of the organization

คนที่ทำหน้าที่กำหนดความปลอดภัยให้กับฐานข้อมูลคือ DBA

- The DBA is responsible for the overall security of the database system.

1.2 Database Security and the DBA (2)

- The DBA has a DBA account in the DBMS
 - Sometimes these are called a system or superuser account
 - These accounts provide powerful capabilities such as:
 - 1. Account creation
 - 2. Privilege granting
 - 3. Privilege revocation (ยกเลิก)
 - 4. Security level assignment
 - Action 1 is access control, whereas 2 and 3 are discretionary and 4 is used to control mandatory authorization

1.3 Access Protection, User Accounts, and Database Audits

- Whenever a person or group of person need to access a database system, the individual or group must first apply for a user account.
 - The DBA will then create a new **account id and password** for the user if he/she deems (ถือว่า) there is a legitimate (มีสิทธิอันชอบธรรม) need to access the database
- The user must log in to the DBMS by entering account id and password whenever database access is needed.

1.3 Access Protection, User Accounts, and Database Audits(2)

- The database system must also keep track of all operations on the database that are applied by a certain user throughout each login session.
 - To keep a record of all updates applied to the database and of the particular user who applied each update, we can modify **system log**, which includes an entry for each operation applied to the database that may be required for recovery from a transaction failure or system crash.

1.3 Access Protection, User Accounts, and Database Audits(3)

- If any tampering (มีแนวโน้มน) with the database is suspected (น่าสงสัย), a database audit is performed
 - A database audit consists of reviewing the log to examine all accesses and operations applied to the database during a certain time period.
- A database log that is used mainly for security purposes is sometimes called an **audit trail**.

Discretionary Access Control Based on Granting and Revoking Privileges

- The typical method of enforcing discretionary access control in a database system is based on the granting and revoking privileges.

2.1 Types of Discretionary Privileges

- **The account level:**
 - At this level, the DBA specifies the particular privileges that each account holds independently of the relations in the database.
- **The relation level (or table level):**
 - At this level, the DBA can control the privilege to access each individual relation or view in the database.

2.1 Types of Discretionary Privileges(2)

- The privileges at the **account level** apply to the capabilities provided to the account itself and can include
 - the **CREATE SCHEMA** or **CREATE TABLE** privilege, to create a schema or base relation;
 - the **CREATE VIEW** privilege;
 - the **ALTER** privilege, to apply schema changes such adding or removing attributes from relations;
 - the **DROP** privilege, to delete relations or views;
 - the **MODIFY** privilege, to insert, delete, or update tuples;
 - and the **SELECT** privilege, to retrieve information from the database by using a **SELECT** query.

2.1 Types of Discretionary Privileges(3)

- The second level of privileges applies to the **relation level**
 - This includes **base relations** and virtual (**view**) relations.
- The granting and revoking of privileges generally follow an authorization model for discretionary privileges known as the access matrix model where
 - The **rows** of a matrix M represents **subjects** (users, accounts, programs)
 - The **columns** represent **objects** (relations, records, columns, views, operations).
 - Each position $M(i,j)$ in the matrix represents the types of privileges (read, write, update) that **subject i** holds on **object j** .

2.1 Types of Discretionary Privileges(4)

- To control the granting and revoking of relation privileges, each relation R in a database is assigned and **owner account**, which is typically the account that was used when the relation was created in the first place.
 - The owner of a relation is given all privileges on that relation.
 - In SQL2, the DBA can assign an owner to a whole schema by creating the schema and associating the appropriate authorization identifier with that schema, using the **CREATE SCHEMA** command.
 - The owner account holder can **pass privileges** on any of the owned relation to other users by **granting** privileges to their accounts.

2.1 Types of Discretionary Privileges(5)

- In SQL the following types of privileges can be granted on each individual relation R:
 - **SELECT** (retrieval or read) privilege on R:
 - Gives the account retrieval privilege.
 - In SQL this gives the account the privilege to use the **SELECT** statement to retrieve tuples from R.
 - **MODIFY** privileges on R:
 - This gives the account the capability to modify tuples of R.
 - In SQL this privilege is further divided into **UPDATE**, **DELETE**, and **INSERT** privileges to apply the corresponding SQL command to R.
 - In addition, both the **INSERT** and **UPDATE** privileges can specify that only certain attributes can be updated by the account.

2.1 Types of Discretionary Privileges(6)

- In SQL the following types of privileges can be granted on each individual relation R (contd.):
 - **REFERENCES** privilege on R:
 - This gives the account the capability to **reference** relation R when specifying integrity constraints.
 - The privilege can also be **restricted** to specific attributes of R.
- Notice that to create a **view**, the account must have **SELECT** privilege on all relations involved in the view definition.

2.2 Specifying Privileges Using Views

- The mechanism of **views** is an important discretionary authorization mechanism in its own right. For example,
 - If the owner A of a relation R wants another account B to be able to retrieve only some fields of R, then A can create a view V of R that includes only those attributes and then grant SELECT on V to B.
 - The same applies to limiting B to retrieving only certain tuples of R; a view V' can be created by defining the view by means of a query that selects only those tuples from R that A wants to allow B to access.

2.3 Revoking Privileges

- In some cases it is desirable to grant a privilege to a user temporarily. For example,
 - The owner of a relation may want to grant the **SELECT** privilege to a user for a specific task and then revoke that privilege once the task is completed.
 - Hence, a mechanism for **revoking** privileges is needed. In SQL, a **REVOKE** command is included for the purpose of **canceling privileges**.

2.4 Propagation of Privileges using the GRANT OPTION

- Whenever the owner A of a relation R grants a privilege on R to another account B, privilege can be given to B with or without the **GRANT OPTION**.
- If the **GRANT OPTION** is given, this means that B can also grant that privilege on R to other accounts.
 - Suppose that B is given the **GRANT OPTION** by A and that B then grants the privilege on R to a third account C, also with **GRANT OPTION**. In this way, privileges on R can **propagate** to other accounts without the knowledge of the owner of R.
 - If the owner account A now revokes the privilege granted to B, all the privileges that B propagated based on that privilege should automatically be revoked by the system.

2.5 An Example

- Suppose that the DBA creates four accounts
 - A1, A2, A3, A4
- and wants only A1 to be able to create base relations. Then the DBA must issue the following GRANT command in SQL

```
GRANT CREATETAB TO A1;
```

- In SQL2 the same effect can be accomplished by having the DBA issue a **CREATE SCHEMA** command as follows:

```
CREATE SCHEMA EXAMPLE AUTHORIZATION A1;
```

2.5 An Example (2)

- User account A1 can create tables under the schema called **EXAMPLE**.
- Suppose that A1 **creates** the two base relations **EMPLOYEE** and **DEPARTMENT**
 - A1 is then **owner** of these two relations and hence all the relation privileges on each of them.
- Suppose that A1 wants to grant A2 the privilege to insert and delete tuples in both of these relations, but A1 does not want A2 to be able to propagate these privileges to additional accounts:

**GRANT INSERT, DELETE ON
EMPLOYEE, DEPARTMENT TO A2;**

2.5 An Example (3)

EMPLOYEE

Name	<u>Ssn</u>	Bdate	Address	Sex	Salary	Dno
------	------------	-------	---------	-----	--------	-----

DEPARTMENT

<u>Dnumber</u>	Dname	Mgr_ssn
----------------	-------	---------

Figure 24.1

Schemas for the two relations EMPLOYEE and DEPARTMENT.

2.5 An Example (4)

- Suppose that A1 wants to allow A3 to retrieve information from either of the two tables and also to be able to propagate the SELECT privilege to other accounts.
- A1 can issue the command:

```
GRANT SELECT ON EMPLOYEE, DEPARTMENT  
TO A3 WITH GRANT OPTION;
```

- A3 can grant the **SELECT** privilege on the **EMPLOYEE** relation to A4 by issuing:

```
GRANT SELECT ON EMPLOYEE TO A4;
```

- Notice that A4 can't propagate the SELECT privilege because GRANT OPTION was not given to A4

2.5 An Example (5)

- Suppose that A1 decides to revoke the SELECT privilege on the EMPLOYEE relation from A3; A1 can issue:
REVOKE SELECT ON EMPLOYEE FROM A3;
- The DBMS must now automatically revoke the SELECT privilege on EMPLOYEE from A4, too, because A3 granted that privilege to A4 and A3 does not have the privilege any more.

2.5 An Example (6)

- Suppose that A1 wants to give back to A3 a limited capability to SELECT from the EMPLOYEE relation and wants to allow A3 to be able to propagate the privilege.
 - The limitation is to retrieve only the NAME, BDATE, and ADDRESS attributes and only for the tuples with DNO=5.
- A1 then create the view:

```
CREATE VIEW A3EMPLOYEE AS  
SELECT NAME, BDATE, ADDRESS  
FROM EMPLOYEE  
WHERE DNO = 5;
```

- After the view is created, A1 can grant **SELECT** on the view A3EMPLOYEE to A3 as follows:

```
GRANT SELECT ON A3EMPLOYEE TO A3  
WITH GRANT OPTION;
```

2.5 An Example (7)

- Finally, suppose that A1 wants to allow A4 to update only the SALARY attribute of EMPLOYEE;
- A1 can issue:

**GRANT UPDATE ON EMPLOYEE (SALARY) TO
A4 ;**

- The **UPDATE** or **INSERT** privilege can specify particular attributes that may be updated or inserted in a relation.
- Other privileges (**SELECT**, **DELETE**) are not attribute specific.

Summary

- 1 Database Security and Authorization
- 2 Discretionary Access Control